

Email as (real) files

Francisco J. Ballesteros

Laboratorio de Sistemas

nemo@lsub.org



© Francisco J. Ballesteros – mail2fs

Oct 12, 2009

Pg. 1

Motivation

- Mail is complex
- Reading is easy
- We need structure
 - ...but that's already implemented



Example mail

From: sheldom@lsub.org

To: nemo@lsub.org

Date: Sun Oct 11 22:58:19 CET 2009


Subject: new episode

Hi, there's a new episode of mine
right here.

! - episode.avi



Idea: keep just that.



Implementation

- Who keeps this?
 - The file system
- Formats?
 - text: text
 - attachments: decoded files



Software?

- Mail reader:
 - Acme, O/live, cat, ...
- Mail search
 - grep, looktags, ...
- Archive mails (same for spam, etc.):
 - mv 3456 a.3456



Problems...

- Scaling
 - Directory per month.
- Replying ids, debugging
 - Raw file with headers
- Too many files to read
 - Use listings



Mailbox format

```
msgs
200901
  1
    raw
    text
    attach.pdf...
  2...
    a.3...      (archived)
    s.4...      (spam)
  200901.1    (cached listing)
  seq
  digest
  folder1...  (custom listing)
```



Virtual folders

- Group messages for the user
- Just a listing of mails
- Creation by cut&paste

200910/a.1870/text

200910/a.1869/text

Pablo Lista

Pedro Problems



Some software needed

- Convert to Plan B format
 - mail2fs
- Generate indexes
 - mails (it's its own cache).
- Convenience
 - Acme reader(not needed in o/live)
 - Scripts



Example guide

Mails | Arch

x/text | Out/D

| Reply | Spam

> grep 9fans >9fans

| sort +2



Example

Remove spam

```
rm -r */s.*
```

Rename an attachment

```
mv 1.gif eagle.gif
```



Example

Locate mails about mail2fs:

```
; looktags nemo msgs mail2fs
/mail/box/nemo/msgs/200801/a.9955/text
/mail/box/nemo/msgs/200801/a.9955/raw
/mail/box/nemo/msgs/200801/a.9937/text
/mail/box/nemo/msgs/200801/a.9937/raw
/mail/box/nemo/msgs/200801/a.9937/1.mail2fs.c
...
.
```



Example

Plumb all attachments from Glenda

```
; for (f in `mails | grep Glenda |  
    awk '{print $1}'`/*.*.pdf)  
plumb $f
```



Performance

time(1) of 25777 messages; 5 not archived.

- On file server:

0.01u 0.01s 0.97r mails

- From home, mounted:

0.00u 0.00s 66.18r mails

- From home, bind -b of month listings

0.00u 0.00s 14.46r mails



The most important point

Mail text and attachments are **real** files.

They can be handled as such.

- We can do that with virtual files, but
 - No software is better software
 - Real files admit more operations

